



Drainage via drain box, vertical connection

Loading:
walkable, wheelchair accessible



Category according to EN 1433 / DIN 19580		A 15	B 125	C 250	D 400**	E 600**	F 900**	Applying to following systems: DACHFIX STEEL 115, 135, 155, 205, 255				
Foundation: width x / height y / thickness z (in cm)												
EN 206-1 / DIN 1045-2	quality of concrete stretcher											
	without danger of frost on the lateral support											
The named concrete quality is a minimum quality												
<p>The installation examples / advise constantly are adapted to the technical conditions. With new editions older expenditures lose their validity. Before planning or installation please verify the current version at www.hauraton.com In building construction is a sealing layer below the channels necessary.</p> <p>The installation example represents a proven recommendation from HAURATON. The final responsibility for the execution lies with the planner in charge. Specific conditions of the project must be taken into account.</p> <p>** Installation situations of drainage systems with high dynamic loads (e.g. airports, motorways and manoeuvring areas of buses, lorries and forklifts, etc.) are not sufficiently considered in DIN EN 1433. Please contact us for such applications to work out project-specific solutions.</p>				Date: 03.06.2022		Our general installation instructions apply.		Format DIN	A4			
								scale	1:6			
						0000088601_BRITISH.dwg		13	EBBw		 Unit 4, Frenchs Avenue LU6 1BH Dunstable / Bedfordshire United Kingdom Tel. +44 1582 501380 TS-UK@hauraton.com	
						DF-STEEL Einbaubeispiel Fassaden, Ein-/Ausgänge Entwässerung über Ablaufbox						