



Installation Example
Concrete Class E 600 - F 900



* y = Component height plus camber

Reinforcement see reinforcement drawing 0000122643

Category according to EN 1433 / DIN 19580		A 15	B 125	C 250	D 400**	E 600**	F 900**	Applying to following systems:				
Foundation: width x / height y / thickness z (in cm)						20 / * / 20	20 / * / 20	RECYFIX HICAP 10300 Access Element				
EN 206-1 / DIN 1045-2 The named concrete quality is a minimum quality	quality of concrete stretcher					C35/45 XD3, XF4, XM2	C35/45 XD3, XF4, XM2					
	without danger of frost on the lateral support					C35/45 XD3, XF4, XM2	C35/45 XD3, XF4, XM2					
	with danger of frost on the lateral support					C35/45 XD3, XF4, XM2	C35/45 XD3, XF4, XM2					
The installation examples / advise constantly are adapted to the technical conditions. With new editions older expenditures lose their validity. Before planning or installation please verify the current version at www.hauraton.com In building construction is a sealing layer below the channels necessary.						Date: 07.01.2022		Our general installation instructions apply.		Format DIN	A4	 Unit 4, Frenchs Avenue LU6 1BH Dunstable / Bedfordshire United Kingdom Tel. +44 1582 501380 TS-UK@hauraton.com
The installation example represents a proven recommendation from HAURATON. The final responsibility for the execution lies with the planner in charge. Specific conditions of the project must be taken into account.								scale		1:15		
** Installation situations of drainage systems with high dynamic loads (e.g. airports, motorways and manoeuvring areas of buses, lorries and forklifts, etc.) are not sufficiently considered in DIN EN 1433. Please contact us for such applications to work out project-specific solutions.						0000104756_BRITISH.dwg		13	EBBw			
						RF-HICAP-10300 Typ 860 mit Revi Aufsatz H300 Einbaubeispiel Klasse E 600 in Beton						